

Base End

Rod End

HAUKAAS FIELD MARKERS

(THE FOLLOWING IS A LIST OF PARTS TO CORRESPOND WITH THE DRAWINGS ON THE PREVIOUS PAGES.)

| Drw# | Part# | Description |
|------|-------------|--|
| 1 | BRG-2207 | 1-1/4" BEARING C/W LOCKING COLLAR |
| 2 | BRG-2209 | 1" BEARING C/W LOCKING COLLAR |
| 3 | BRG-2450 | 1-1/4" BEARING & HOUSING COMPLETE |
| 4 | BRG-2463 | 1-1/4" BEARING HOUSING ONLY |
| 5 | BRG-2476 | 1" BEARING & HOUSING COMPLETE (2 BLT) |
| 6 | BRG-2486 | 1" BEARING HOUSING ONLY (2 BLT) |
| 7 | BRG-2866 | 1" BEARING HOUSING ONLY (4 BOLT) |
| 8 | BRG-2867 | 1" BEARING ONLY (4 BOLT) |
| 9 | FNS-02290 | 5/8" U-BOLT FOR 4x4" SQ. TUBE |
| 10 | FNS-02357 | 1/2" U-BOLT FOR 3x3" SQ. TUBE |
| 11 | FNS-02392 | 5/8-11x6" I-BOLT (4" THREAD) |
| _ | FNS-02531 | 3/8"x16x3/8"SETSCREW |
| _ | FNS-110B5PC | 5/16 x 1/2" GR. 5 HEX BOLT |
| | FNS-112-5PC | 5/16x2" GR. 5 HEX BOLT |
| | FNS-112-8PC | 5/16x2" GR. 8 HEX BOLT |
| | FNS-113B5PC | 5/16x3-1/2" GR. 5 SHEAR BOLT |
| | FNS-131B5PC | 7/16x1-1/2" GR. 5 SHEAR BOLT |
| | FNS-132-5PC | 7/16x2" GR. 5 HEX BOLT PLT |
| | FNS-140C5PC | AND |
| | FNS-141-5PC | 1/2 x 1" GR. 5 HEX BOLT |
| | FNS-142C5PC | 1/2x2-3/4" GR. 5 HEX BOLT |
| | FNS-143-5PC | 1/2 x 3" GR. 5 HEX BOLT |
| | FNS-143C8PC | 1/2x3-3/4" GR. 8 HEX BOLT |
| | FNS-144B5PC | 1/2x4-1/2" STOP BOLT |
| | FNS-165B5PC | 5/8x5-1/2" GR. 5 HEX BOLT |
| | FNS-172-5PC | 3/4 x 2" GR. 5 HEX BOLT |
| | FNS-173B5PC | 3/4x3-1/2" GR. 5 HEX BOLT |
| | FNS-195B5PC | 1" x 5-1/2" GR. 5 HEX BOLT |
| | FNS-197-5PC | 1" x 7" GR. 5 HEX BOLT |
| | FNS-221B5PC | 3/8x1-1/2" GR. 5 CARRIAGE BOLT |
| | FNS-241A5PC | 1/2x1-1/4" GR. 5 CARRIAGE BOLT |
| | FNS-241B5PC | 1/2x1-1/2" GR. 5 CARRIAGE BOLT |
| | FNS-241C5PC | 1/2x1-3/4" GR. 5 CARRIAGE BOLT |
| - | FNS-3685PC | 5/8"x8"NC GR. 5 SPADE BLT |
| | FNS-54JPC | 1/2"- 13 NC JAM NUT |
| _ | FNS-54LPC | 1/2"- 13 NC NYLON LOCKNUT |
| _ | FNS-54RPC | 1/2"-13 NC HEX NUT |
| | FNS-57LPC | 3/4"- NC NYLON LOCKNUT |
| _ | FNS-57SPC | 3/4"-10 STOVER NUT |
| | FNS-59JPC | 1" - 8 JAM NUT PLT |
| | FNS-593FC | 1"-8 HEX NUT PLT |
| _ | FNS-59SPC | 1"-8 STOVER NUT PL |
| | FNS-69RP | 1" LOCK WASHER PLT |
| | FNS-74RP | 1/2" FLAT WASHER PLT |
| | FNS-79NP | 1" FLAT WASHER PLT |
| | FNS-79RP | 1" FLAT WASHER SAE |
| | FNS-82CPC | 3/8x3/4" SQ HD SET SCREW |
| _ | FNS-8A41BPC | 1/2 x1-1/2"SQ HD SET SCREW |
| | FNS-8CB-1BP | 3/16 x 1-1/2 COTTER-PIN |
| | FNS-96SLN | 5/8" STOVER LOCK NUT |
| | HP-9JF026 | 1/4"HOSEx26" 9/16" FEMALE JIC |
| _ | HP-9JF032 | The state of the s |
| | | 1/4"HOSEx32" 9/16" FEMALE JIC |
| 33 | HYD-2368 | HYDRAULIC CYLINDER |

HAUKAAS FIELD MARKERS

(THE FOLLOWING IS A LIST OF PARTS TO CORRESPOND WITH THE DRAWINGS ON THE PREVIOUS PAGES.)

| E4 | TUVD 2515 | 0/46" UC MyEyE TEE |
|----|--------------|---|
| 54 | HYD-2515 | 9/16"JIC MXFXF TEE |
| 55 | HYD-2516 | 1/4"MALE NPT->9/16"MALE JIC 90 DEG ELBOW |
| 56 | HYD-2528 | CYLINDER PIN KIT |
| 57 | HYD-2888 | 1/2"MALE NPT->3/8"FEMALE NPT 90 DEG ELBOW |
| 58 | HYD-2890 | 1-1/2"x4" HYDRAULIC CYLINDER (3000PSI) |
| 59 | HYD-2891 | 3/8"MALE NPT->9/16"-18MALE JIC STRAIGHT |
| 60 | HYD-2892 | 3/8"MALE NPT->#6MALE JIC TEE |
| 61 | HYD-2893 | 1/2"MALE NPT->3/8"MALE NPT 90 DEG ELBOW |
| 62 | HYD-2894 | 1/4"x11-1/2" HOSE 1/4"MALE NPT->#6FEMALE JIC 9/16"-18 |
| 63 | HYD-2895 | 3/8" BALL VALVE |
| 64 | HYD-2896 | PILOT OPERATED CHECK VALVE |
| 65 | MIS-2192 | NYLON DEPTH GUAGE |
| 66 | MIS-2195 | SHOCK ABSORBER |
| 67 | MIS-2325 | GF641 GREASE ZIRK |
| 68 | MIS-2362 | RUBBER BUMPER PAD |
| 69 | MIS-2526 | 18" NOTCHED DISC BLADE |
| 70 | SA-8051L | SMALL SUB-FRAME LEFT |
| 70 | SA-8051R | SMALL SUB-FRAME RIGHT |
| 71 | SA-8052L | SMALL MAIN FRAME LEFT |
| 71 | SA-8052R | SMALL MAIN FRAME RIGHT |
| 72 | SA-8053/136L | PRIMARY ARM 136 LEFT |
| 72 | SA-8053/136R | |
| 72 | SA-8053/246L | PRIMARY ARM 246 LEFT |
| 72 | SA-8053/246R | PRIMARY ARM 246 RIGHT |
| 72 | SA-8053/286L | PRIMARY ARM 286 LEFT |
| 72 | SA-8053/286R | PRIMARY ARM 286 RIGHT |
| 73 | SA-8054/136 | 136 CABLE 88" OVERALL |
| 73 | SA-8054/246 | 246 CABLE 112" OVERALL |
| 73 | SA-8054/286 | 286 CABLE 124" OVERALL |
| 73 | SA-8054/356 | 356 CABLE 134" OVERALL |
| 73 | SA-8054/466 | 466 CABLE 158" OVERALL |
| 74 | SA-8055 | THIRD STAGE ARM |
| 75 | | |
| 76 | SA-8056 | DISC ASSEMBLY BRACKET |
| | SA-8057 | SMALL SPROCKET ASSEMBLY (4 HOLE) |
| 77 | SA-8065 | END BUSHING BRACKET ASSEMBLY |
| 78 | SA-8066 | 3" CABLE PULLEY |
| 79 | SA-8067 | HYDRAULIC CYLINDER ANCHOR BRACKET |
| 80 | SA-8069 | CABLE CLEVIS BOLTS |
| 81 | SA-8082 | CABLE/CLEVIS BUSHING (1/2") |
| 82 | SA-8084 | DISC AXLE |
| 83 | SA-8085 | 1/2 LINK BUSHING 11/16" |
| 84 | SA-8086 | SMALL ANGLE IRON ASSEMBLY (4 HOLE) |
| 85 | SA-8087/136 | 136 2ND STAGE ARM TUBE ASSEMBLY |
| 85 | SA-8087/246 | 246 2ND STAGE ARM TUBE ASSEMBLY |
| 85 | SA-8087/286 | 286 2ND STAGE ARM TUBE ASSEMBLY |
| 86 | SA-8088 | #80 ROLLER CHAIN (18 PINS-20" LONG) |
| 87 | SA-8104/356L | PRIMARY ARM 356 LEFT |
| 87 | SA-8104/356R | PRIMARY ARM 356 RIGHT |
| 87 | SA-8104/466L | PRIMARY ARM 466 LEFT |
| 87 | SA-8104/466R | PRIMARY ARM 466 RIGHT |
| 88 | SA-8109L | END BUSHING BRACKET ASSEMBLY LEFT |
| 88 | SA-8109R | END BUSHING BRACKET ASSEMBLY RIGHT |
| 89 | SA-8118/356 | 356 2ND STAGE ARM TUBE ASSEMBLY |
| 89 | SA-8118/466 | 466 2ND STAGE ARM TUBE ASSEMBLY |

HAUKAAS FIELD MARKERS


(THE FOLLOWING IS A LIST OF PARTS TO CORRESPOND WITH THE DRAWINGS ON THE PREVIOUS PAGES.)

| 90 | SA-8182 | STABILIZER SPRING ANCHOR RING |
|-----|--|--|
| 91 | SA-8183 | STABILIZER SPRING LIFT BOLT/BUSHING |
| 92 | SA-8184 | CABLE CLIP |
| 93 | SA-8195 | LG ANGLE IRON ASSEMBLY (8 HOLE) |
| 94 | SA-8196 | LG SPROCKET ASSEMBLY (8 HOLE) |
| 95 | SA-8218 | 3/8" EXTENDED HALF LINK |
| 96 | SA-8219 | 3/8" CABLE/CHAIN HALF LINK |
| 97 | SA-8221 | STABILIZER ARM PIVOT ASSEMBLY |
| 98 | SA-8222 | TUBE LOCK LATCH |
| 99 | SA-8223 | 1" SQUARE TUBE DISC GUARD |
| 100 | SA-8224 | AUTO-LOCK LATCH |
| 101 | SA-8335 | SM ANGLE IRON ASSEMBLY (8 HOLE) |
| 102 | SA-8336 | SM SPROCKET ASSEMBLYY (8 HOLE) |
| 103 | SA-8337L | 466 MAIN FRAME LEFT |
| 103 | SA-8337R | 466 MAIN FRAME RIGHT |
| 104 | SA-8338L | LARGE SUB-FRAME LEFT |
| 104 | SA-8338R | LARGE SUB-FRAME RIGHT |
| 105 | SA-8339 | MAIN FRAME SHAFT (1-1/4" COLD ROLLED 14" LONG) |
| 106 | SA-8340 | STABILIZER ARM ASSEMBLY |
| 107 | SA-8381 | SL-HYD LIFT BRACKET 466 |
| 108 | SA-8385 | TUBE LOCK LATCH (LARGE MARKERS) |
| 109 | SA-8400 | 8x1.25x8MM SET SCREW 3/64" ORIFICE |
| 110 | SA-8417 | SM STABILIZER TUBE ARM ASSEMBLY |
| | SA-8418 | SM STABILIZER WEB ARM ASSEMBLY |
| | SA-8419 | SM STABILIZER ARM PEDISTAL |
| | SA-8420 | SM STABILIZER ARM SPRING/ANCHOR ASSEMBLY |
| 114 | SA-8421 | SM STABILIZER CENTRE PIN ASSEMBLY |
| 115 | A STATE OF THE PARTY OF THE PAR | STAB/I-BOLT HOLDER |
| | SPR-2173 | LARGE CB SPRING |
| 117 | SPR-2315 | SMALL CB SPRING |
| | SPR-2395 | MEDIUM CB SPRING |
| | SPR-2498 | X-LARGE CB SPRING |
| 120 | WHL-2172 | 3" NYLON WHEEL |
| | | |

SA-17ASK SEQUENCE VALVE

IMPORTANT! ORIFICE INSIDE FITTING AT BASE END PORT OF CYLINDER SHOULD BE REMOVED ON MODELS 136, 246, 286 AND 356 MARKERS.

BUT DO NOT REMOVE ORIFICE ON MODEL 466 MARKERS!!



The following are the instructions for plumbing a SHOEMAKER Sequencing Valve with the SIDE ARM Field Markers.

On the valve you will find stamped: R and C. Plumb the valve in as follows: Front Ports - Connects to the hydraulics on tractor.

Port C -Connects to the BASE end port on the hydraulic cylinder. (Ball valve side)

Port R -Connects to the ROD end port on the cylinder. (Check-valve side)

The best location for the valve would be close to the point where the left side of the hitch joins to the center section of the implement. Use the supplied bracket to fasten the valve to the frame of implement.

From the valve there will be two hoses running to the tractor and two hoses running to each marker, (6 hoses in all)

We recommend 3/8" hose be used. Use 9/16" JIC female ends.

Note: Warranty is void if Teflon tape is used.

Note: The fine threaded bolts on the valve then can be adjusted to regulate the speed of the markers. It is possible to slow the oil flow down too much with this adjustment which will cause the valve not to sequence. Do not screw flow adjustment all the way out of valve body as damage to seals may result.

Parts List for SA-17ASK

- 1 Shoemaker Sequence Valve (gold in color)
- 1 Valve Bracket (3715) 1 -Instruction Sheet
- 1 4" x 5/8" U-bolt 2 3/8" x 1" Hex Bolts
- 2 5/8" Nuts
- 2 3/8" Lock washers
- 2 5/8" Lock washers

Parts List for SHOEMAKER VALVE

Item A - 9/16" JIC Straight Connector - HYD-2510

Item B - Spool - HYD-2509

Item C - Adjustment Assembly (Flow) - HYD-2508

Item D - Special C Fitting x 9/16" JIC - HYD-2481

Item E - Seal, Spring and Ball Kit - HYD-2507